

Non-Toxic, OEM Compliant Metal Protection




A Surface-Active Metal Passivation Technology
For Low, Medium & High Pressure Boilers

HOW DOES IT WORK ?


Video Example of No Surface-Active Chemistry Protection

Hydrophilic Oxide



Surface Active Chemistry SAC

Stage 1 (real site images illustrating this stage next)



- Anodamine Permeation Through Oxide to Virgin Base Metal
- Cycle Clearance – Release of Trapped Inorganics, (Cation Conductivity Change).
- Limited Visual Topotactic Hydrophobicity
- Base Metal Protection & Hydrophobicity


Surface Active Chemistry SAC

Stage 1 (real site images illustrating this stage next)



Surface Active Chemistry SAC

Step 2 (real site images illustrating this stage next)



- Partial Epitactic Hydrophobicity
- Epitactic Oxide Free of Inorganic Contamination
- Base Metal Topotactic Hydrophobicity
- Base Metal Protection

Surface Active Chemistry SAC




Surface Active Chemistry SAC

Cycle Clearance and Transformation of Surface Oxide


1,900 psi / 131 bar 1,055 °F / 566 °C Re-heat Steam

Mixed Metallurgy Cycle



Surface Active Chemistry SAC

Step 2 (real site images illustrating this stage next)



- Partial Epitactic Hydrophobicity
- Epitactic Oxide Free of Inorganic Contamination
- Base Metal Topotactic Hydrophobicity
- Base Metal Protection


Surface Active Chemistry SAC



Surface Active Chemistry SAC

Stage 3

(real site images illustrating this stage next)



- Achieved With Continuous 1000 – 1500 ppb Equilibrium Residual
- When Stage 3 is Achieved, (Time Dependent on Total Available Surface Area)
 - Dosage Can Be Reduced to Maintain 800 – 1000 ppb
- Complete Oxide Hydrophobicity
- Higher 3+ Oxide Content
- Base Metal Protection

Surface-Active Chemistry (SAC)

Video Example of Stage 3 Protection



Re-heat Tube (carbon steel) from a 3,600 psi / 870 MW Super-critical Once-through Unit with full-flow Powdex polishers. The unit was commissioned in 1974 and was converted from Oxygenated chemistry to Anodamine AVT(O). The steam touched oxide was lightly sanded to expose the tube material.



Surface Active Chemistry SAC

Conventional Film Forming Amines


Conventional Film Forming Amines

FILM FORMING AMINES

- Mechanism of treatment is vastly different
- Do some treat the critical 2-phase locations.
- Are they OEM steam quality compliant?
- Selectivity of film formation?
- Compare MSDS.
- Check product toxicity LD50 aquatic organisms.
- Are they retained by soils, environmental concerns?
- Check product handling concerns.
- Check product flash point and flammability.
- Observe product solubility in water.
- Does the product contain neutralizing and/or alkalizing amines.....etc

Limitations of Conventional FFAs

- **Non** OEM Compliant, **increased** CACE > 0.2uS/cm
- **Non-selective** film formation
- Dangerous **trapping** of inorganic contaminants
- **Under Deposit Corrosion** – base metal attack
- Degradation products (**waxy slime balls**)
- Film **degradation**



Limitations of Conventional FFAs



Conventional FFA

Limitations of Conventional FFAs



Due to differences in volatility and solubility between neutralizing amines and “all FFA chemistries” when neutralizing amines are lost, the FFA becomes insoluble in water and generates solids and/or a micro emulsion.

Surface Active Chemistry SAC

BENEFITS ?



Surface Active Chemistry SAC

BENEFITS OF USING **ANODAMINE**

1. Reduced/Elimination of both single and 2 phase FAC
2. Reduced/Eliminate Chemistry Holds.
3. No Chemistry Related Boiler Tube Failures.
4. No special layup precautions, Ability to layup wet or dry.
5. Potential to Eliminate Boiler Cleanings.
6. Improved Reliability & Availability, Irrespective of Mode of Operation.
7. No Negative Effect on CPP (Powdex or Whole Bead Polishers)

The background features a large, light gray circle centered on the page. Overlaid on this circle is a white chemical structure, which appears to be a complex organic molecule with several rings and functional groups. A dark blue horizontal band spans the width of the image, positioned across the middle of the circle and the chemical structure.

REDUCED CHEMISTRY HOLDS




Installation Data

- 3 x 3,600 psi / 248 bar, CE super-critical once-through unit with a 870 WH Turbines. The unit was commissioned between 1978 and 1980. The condensate is passed through full-flow Powdex polishers. HP steam is reheated to 1,050 °F / 566 °C.
- Boiler feedwater is deaerated.
- The units were converted to Anodamine / OT and ammonia chemistry in 2013.

Reduction in TOTAL Iron Transport


Super-critical Once Through Boiler with Powderx
593 MW 3,600 psi / 248 bar (1,055°F / 568 °C)



Ferrozine® ULR Method – TOTAL Iron LDL 0.3ppb; Adapted from Stookey, L.L.,
Anal. Chem., 42(7), 779 (1970)

Reduction in DISSOLVED Iron Transport


Super-critical Once Through Boiler with Powdex
593 MW 3,600 psi / 248 bar (1,055°F / 568 °C)



Ferrozine® ULR Method – TOTAL Iron LDL 0.3ppb; Adapted from Stookey, L.L.,
Anal. Chem., 42(7), 779 (1970)


Cation Conductivity / Cycle Clearance

Super-critical Once Through Boiler with Powdex
593 MW 3,600 psi / 248 bar (1,055°F / 568 °C)



Corrosion Product Transport during Cyclic Load Operation

593 MW 3,500psi / 241 bar,
1,055 °F / 566 °C Re-heat steam




Ferrozine® ULR Method – TOTAL Iron LDL 0.3ppb, digested using DRB 200 (30 minutes) and reading on DR 3900 with pour-through cell.

Typical corrosion product transport with OT / Ammonia chemistry was between 1 and 25 ppb. Under the same operating conditions with Anodamine chemistry, the total iron in the feedwater, superheat and reheat steam is < 0.5 ppb.

Reduction in Corrosion Product Transport during Unit return-to-service

593 MW 3,500psi / 241 bar,
1,055 °F / 566 °C Re-heat steam

Unit return to service with Conventional Chemistry, typical 4 days



The unit typically remained in
chemistry hold for days before the
cycle chemistry complied for Turbine
(estimated operation cost in excess of US 100,000 per hour)



Please note. Due to extremely high corrosion product transport, some Millipore pads only represent 200 ml samples instead of 1 liter.

Unit return to service with Surface Active Chemistry, typical 4 hours



Elimination
of chemical
hold periods

Surface Active Chemistry SAC

Using Anodamine treatment improvements in unit start-ups accompany:

1. reduced oxide transport
2. full steam water cycle protection
3. improved performance of full flow Powdex Polishers

many super critical units are noticing an appreciable reduction in chemistry holds, often **reduced from approx. 2 days down to 4 - 5 hours.**

The financial benefit derived by this performance characteristic can be summarized as follows:

Surface Active Chemistry SAC

- Typical chemistry holds pre-Anodamine range from **2 days** depending on length of outage and success of the layup procedure. Chemistry holds have been reduced to < 5 hours
- Est. 27,000 MW gained due to entire cycle protection, & rapid start using Anodamine.
- Average of x lbs coal per MW produced, coal price \$ x per ton
- = **\$540,000** (Saving in MW produced due to rapid start – excluding contractual dispatch, loss production penalties.)
- = **\$ 130,0000** (Reduction in fired fuel saved due to rapid start) -
\$10,000 of fuel oil burnt per hour whilst on chemistry hold.

*Calculation based on supercritical once through cyclic operation, 840 MW day operation, 450 MW night operation, 3600 psig full flow Powdex polishers. (\$20 per MW)

Surface Active Chemistry SAC

DURING CONTINUED CYCLIC OPERATION (TREATMENT WITH ANODAMINE)

1. Extended Powdex runs between pre-coats (pressure drop)
 - Before: 3 weeks between pre-coats
 - After: 12 weeks between pre-coats
2. Visual change in resin when replacing/pre-coating.
3. Full cycle chemistry compliance.
4. Resultant Savings In Extended Powdex Runs = **\$39,000**
(projected annual savings @ \$3,000 each)

*Calculation based on supercritical once through cyclic operation, 840 MW day operation, 450 MW night operation, 3600 psig full flow Powdex polishers.

Surface Active Chemistry SAC

RETURN TO SERVICE FROM 7 - 8 MONTH EXTENDED OUTAGE
(ROUTINE TREATMENT AND OFFLINE PROTECTION WITH ANODAMINE).

Powdex polisher pre-coats required
on startup (before Anodamine)

35 – 40 pre-coats @ \$3,000 each
\$105,000

Powdex polisher pre-coats required
on startup (treated with Anodamine)

4 – 5 pre-coats @ \$3,000 each
\$13,500

SAVINGS IN POWDEX REPLACEMENT:
\$91,500

*Calculation based on supercritical once through cyclic operation, 840 MW day operation, 450 MW night operation, 3600 psig full flow Powdex polishers.

The background features a large, light gray circle centered on the page. Overlaid on this circle is a white chemical structure, which appears to be a complex organic molecule with several rings and functional groups. A dark blue horizontal band spans the width of the image, positioned across the middle of the gray circle and the chemical structure.

REDUCED CHEMISTRY HOLDS

870MW CCGT, The Netherlands



After only 2.5 months after starting Anodamine dosing, chemical holds have been eliminated and total iron concentrations are all well within OEM compliance.

(LP 2.0 $\mu\text{g/l}$; IP 23 $\mu\text{g/l}$; HP Once Through 5.9 $\mu\text{g/l}$ total Iron).

CCGT START UP COMPARISON WITH SWITCH TO ANODAMINE

LP Feed Water

IP Feed Water

LP Drum

LP Superheater
Steam


Condensate



129 µg/L total iron



14,3 µg/L total iron



25800 µg/L total iron



130 µg/L total iron



829 µg/L total iron

Before
Anodamine



39 days on
Anodamine



21 µg/L total iron




3,5 µg/L total iron



87100 µg/L total iron



22 µg/L total iron



285 µg/L total iron

74 days on
Anodamine



3,7 µg/L total iron



2,1 µg/L total iron



16 µg/L total iron




2,0 µg/L total iron



94 µg/L total iron

870MW CCGT


COLD START COMPARISON WITH SWITCH TO ANODAMINE



■ **BEFORE ANODAMINE** ■ **39 DAYS ANODAMINE** ■ **74 DAYS ANODAMINE**

870MW CCGT

WARM START COMPARISON WITH SWITCH TO ANODAMINE



■ **BEFORE ANODAMINE** ■ **88 DAYS ANODAMINE**

*The outage for both starts was 53 hours. The start-curve used is the same which can be seen in the MW curve for both starts.

Surface Active Chemistry SAC

Calculated annual savings in natural gas = 45,000 Nm³ (per start)

Estimated US natural gas cost \$ 0.2225 Nm³ = **\$10,012 per start.**

(calculated on US industrial pricing) – Netherlands pricing est. \$0.75/Nm³

Reference pricing estimate Public Policy Institute - Source: Energy Information Administration

<http://www.ppiny.org/reports/jtf2004/naturalgas.htm>



IMPROVED RELIABILITY

Preventing Corrosion Fatigue CF




- 1 x 2,600 psi / 179 bar, CE Natural circulation, mixed metallurgy drum units with 475 MW WH Turbines, commissioned in 1964. HP steam is reheated to 1,050 °F / 566 °C.
- 1 x 1,935 psi / 133 bar, B&W Natural circulation, mixed metallurgy drum units with 125 MW GE Turbines, commissioned in 1958. HP steam is reheated to 1,050 °F / 566 °C. (retired)
- Unit 1 is retired, Unit 2 was converted from AVT(R) – Hydrazine / CT to Anodamine / AVT(O) / CT in 2013.
- Unit 2 is a peaking unit operating anywhere from 2 to 20 hours per start-up.
- The unit operates at 10 to 15% of available time.

Unit Failure Frequency

(Hydrazine chemistry = failure every 143 hours)

475 MW 2,600 psi / 179 bar, 1,005°F re-heat
Mixed Metallurgy Drum Unit



The number of times
the unit failed to
return-to-service

Hydrazine Reducing Chemistry


12 failures
(failure every 143 hours)

Anodamine

ZERO failures

Unit Availability on Start-up

475 MW 2,600 psi / 179 bar, 1,005°F re-heat
Mixed Metallurgy Drum Unit



Unit Availability

Hydrazine Reducing Chemistry

81% available on start-up


Anodamine

100% available on start-up

19% gain in unit availability

Reliability and Availability vs. Power Generated

475 MW 2,600 psi / 179 bar, 1,005°F re-heat
Mixed Metallurgy Drum Unit



Power Generated

Hydrazine Reducing Chemistry

213,115 MW generated

Anodamine


242,212 MW generated

29,000 MW
additional Power
Generated

The Cost Of Poor Reliability and Availability

475 MW 2,600 psi / 179 bar, 1,005°F re-heat
Mixed Metallurgy Drum Unit

Data represents approximately 10,000 hrs. on Hydrazine chemistry vs. 10,000 hrs. on Anodamine chemistry



Cost savings with improved availability and reliability

Improved Reliability (No lost time)

U\$ 1,200,000

Additional MW generated with 100% unit availability


U\$ 3,100,000

U\$ 4,300,000



2 PHASE PROTECTION

Anodamine distribution throughout the water steam cycle



HPFG target concentration 800 - 1,000 ppb

The Anodamine chemistry is normally introduced into the condensate pump discharge. With a 50/50 volatile-to-liquid ratio at boiler temperatures, 50% of the product is transferred to the saturated steam. The chemistry is stable to superheat temperatures and will therefore provide surface-active protection of all water and steam touched surfaces throughout the turbine stages, reheat steam and extraction steam to the feedwater heaters. During steam condensation, 50% of the chemistry is transferred to the liquid fluid, providing the necessary surface-active chemistry protection in the two-phase flow locations.

High Intermediate Pressure (HIP) 3rd (Bottom Tubes)

Manufacturer	Foster Wheeler
Date Stamped	1996
Number of Tubes	391
Tube OD (inches)	3/4
Tube Gauge	18 B.W.G.
Tube X-Sec. Area (sq. ft.)	0.002319
Tube Material	Admiralty
Design Feedwater Flow (lb./hr.)	1349655
Design Flow Velocity (ft./sec.)	6.63 @ 60 F


326°F

Tube as received by client

High Intermediate Pressure (HIP) 3rd (Bottom tubes) from a 2,200 psi / 253 MW, 1,000°F / 538°C re-heat steam, natural-circulating, mixed metallurgy drum unit The unit was commissioned in 1963 and was converted from all-volatile-reducing hydrazine chemistry to Anodamine AVT(O). The unit retired for decommission in December 2013. The feedwater heater tubes were removed one year later and sent to our laboratory for inspection. The condition of the tubes as received by the client without preservation or protection.

High Intermediate Pressure (HIP) 3rd (Top Tubes)

Manufacturer	Foster Wheeler
Date Stamped	1996
Number of Tubes	391
Tube OD (inches)	3/4
Tube Gauge	18 B.W.G.
Tube X-Sec. Area (sq. ft.)	0.002319
Tube Material	Admiralty
Design Feedwater Flow (lb./hr.)	1349655
Design Flow Velocity (ft./sec.)	6.63 @ 60 F




326°F

Tube as received by client

High Intermediate Pressure (HIP) 3rd (TOP tubes) from a 2,200 psi / 253 MW, 1,000°F / 538°C re-heat steam, natural-circulating, mixed metallurgy drum unit The unit was commissioned in 1963 and was converted from all-volatile-reducing hydrazine chemistry to Anodamine AVT(O). The unit retired for decommission in December 2013. The feedwater heater tubes were removed one year later and sent to our laboratory for inspection. The condition of the tubes as received by the client without preservation or protection.

High Pressure Cross Over (Top Tubes)


Manufacturer	Yuba
Date Stamped	1988
Number of Tubes	906
Tube OD (inches)	5/8
Tube Gauge	.065 min wall
Tube X-Sec. Area (sq. ft.)	0.001336
Tube Material	C.S.
Design Feedwater Flow (lb./hr.)	1617000
Design Flow Velocity (ft./sec.)	6.11 @ 1.0 SP GR



469°F

Tube as received by client

High Pressure Cross over (TOP tubes) from a 2,200 psi / 253 MW, 1,000°F / 538°C re-heat steam, natural-circulating, mixed metallurgy drum unit The unit was commissioned in 1963 and was converted from all-volatile-reducing hydrazine chemistry to Anodamine AVT(O). The unit retired for decommission in December 2013. The feedwater heater tubes were removed one year later and sent to our laboratory for inspection. The condition of the tubes as received by the client without preservation or protection.




HRSG's & ACC's Protection Single & 2 Phase FAC Using Anodamine

The plant utilizes two highly efficient Siemens-Westinghouse 501FD2 combustion turbines to produce electricity. Additionally, the exhaust from the two turbines is recycled to produce steam for an Alstom STF30C steam turbine to make additional electricity.

- 2 x Alstom Triple pressure HRSG, Steam pressure for LP / IP / HP units is 129 / 721 / 2,781 psi & 9 / 50 / 192 bar. HP steam is reheated to 1,055 °F / 568 °C. Total generation capacity is 530 MW with two 134 MW Alstom Turbines.

Triple Pressure HRSG with ACC's Total Iron Corrosion Product Transport during Two-shifting

Load (MW)




Comments made by group cycle chemist:

This type of operating scenarios is one of the most harsh operating conditions a unit can experience as far as iron transport.

This Triple pressure combined cycle with massive ACC's operates at cyclic load, shutting down during low power demands at night and returning to service during peak demands in the morning. A 0.45 um Millipore sample was collected over a period 24 hours, with unit operation at low load during the day, peaking during high demand and reserve lay-up during the night. Total particulate iron collected was only 2.9 ppb.

Triple Pressure HRSG with ACC's Total Iron Corrosion Product Transport during Two-shifting


0.45 um Millipore pad



**2.9 ppb
Total Iron**

During reserve lay-up the auxiliary boiler provides steam to operate the steam air injector which maintain the vacuum on the boilers. The condensate system provides feed water to the auxiliary boiler and any losses are compensated with make up water. Comments made by group cycle chemist: "This type of operating scenarios is one of the most harsh operating conditions a unit can experience as far as iron transport".

LP turbine exhaust lower distribution duct. The operational environment is supplied with steam having approx. 5 – 6 % moisture, image taken after the LP section of the turbine just prior to steam distribution vanes. The entire lower pipe sections were found wet with lots of water pooling. The unit had been offline for 3 months with no external form of preservation.



Surface Active Chemistry SAC


Air-cooled Condenser Saturated Steam Ducting. Unit had been offline for 3 months with water pooling and no additional form of preservation. The internal environment was found very warm and extremely humid during the inspection.



Entry to "A" Frames of ACC tubes.


No visible signs of FAC in any of the steam flow path areas.

It was reported by site inspections that old areas noted as being previously affected by FAC damage had now been terminated.




Surface Active Chemistry SAC

Entry to "A" Frames of ACC tubes.



Excellent metal protection and hydrophobicity was evident on all metal surfaces and right down in to the high velocity steam flow path



Excellent metal protection and hydrophobicity was evident on all metal surfaces and right down in to the high velocity steam flow path



THANK YOU

+ Questions?