



Towards a broad-spectrum approach to testing modern Air-Cooled Condensers

Air-Cooled Condenser User Group 2025

Dewald Dewet Visser, International Specialized Services Lead

Content

01 Early ACC Tech vs New

02 Air Inleakage Testing

03 Liquid Ring Vacuum Pumps (LRVP)

04 ACC Dephlegmators

05 ACC Operation

06 Dissolved Oxygen

07 Broad Spectrum Approach

01 Early ACC Tech vs New

A perspective on how ACC designs have changed:

- Older ACCs were big, bulky, over-designed and rigid
- Newer designs are smaller, seem to have smaller margins, be structurally more flexible and cost effective

Why would this be the case?

- Market competitiveness
- Higher material, labour and construction costs
- Suppliers being more cost effective to be more competitive



02 Air Inleakage Testing


Most common inleakage areas:

Older ACCs:

- Top and Bottom tube welds on Primary heat exchanger
- Top & Bottom Tube welds between Primary heat exchanger and dephlegmator

Newer ACCs:


- Rupture discs
- Expansion joints
- Glands, shaft seals (Turbine, Vac pumps etc.)
- Flange connections



03 Liquid Ring Vacuum Pump (LRVP) Challenges


The following are typical LRVP challenges

- Inadequate vacuum levels
- High seal water temperatures
- Air or non-condensable ingress
- Cavitation
- Mechanical Damage
- Improper pump operation




03 Liquid Ring Vacuum pump (LRVP) Challenges:

- Mechanical Challenges
- QA/QC Challenges
- LRVP Protection Effectiveness
 - Spray water protection
 - Anti-cavitation Protection



03 Liquid Ring Vacuum pump (LRVP) Challenges: Case Study 1

Mechanical Challenges



03 Liquid Ring Vacuum pump (LRVP) Challenges: Case Study 1


QA/QC Challenges

Observations:

- Inadequate Quality Management System (QMS)
- Inadequate failure investigation reports
- Inadequate pump strip down records
- Unnecessary replacement of pump components




03 Liquid Ring Vacuum pump (LRVP) Challenges: Case Study 2




03 Liquid Ring Vacuum pump (LRVP) Challenges: Case Study 2

Correlation Back Pressure [InHg] & Ambient Temperature [°F], March 2025



Correlation Back Pressure [InHg] & Wind Speed [MPH], March 2025



The effect of wind speed, ambient conditions on ACC Performance

03 Liquid Ring Vacuum pump (LRVP) Challenges: Case Study 2

What are the requirements for optimal operation of LRVP during all seasons?

Requirement	Cold Conditions (<50F°)	Warm Conditions (>95F°)
Seal Liquid Temp Control	Heating or circulation	Cooling via HX or chiller
Freeze Protection	Drainage, insulation, heaters	Not required
Cavitation Risk	Low	High – requires cooling
Material Suitability	Freeze-resistant materials	Heat-resistant materials
Startup/Shut-down Handling	Warm-up, prevent freezing	Avoid hot restart with hot liquid

Optimal control and protection especially during the summer months:

- Ensure effective operation of glycol cooling system to prevent high seal water temperature.
- Ensure effective control of anti-cavitation control valves:
 - Temperature differential between seal water temperature and ambient temperature (**Under investigation**)
 - Using the LRVP suction pressure to control the modulating anti-cavitation valve to prevent vapour pressure conditions that would result in cavitation. (**Under Investigation**)




04 Air-Cooled Condenser Dephlegmators

The Whiskey distillery of the energy Industry:





- Both rely on phase change and effective heat transfer
- Both require tight temperature and pressure control
- Cooling is central to both processes



04 Air-Cooled Condenser Dephlegmators



04 Air-Cooled Condenser Dephlegmators



04 Air-Cooled Condenser Dephlegmators

How do we go about resolving this?

Step 1: Air in leakage testing

Step 2: Effective LRVP or Ejector system testing

Step 3: Investigate the possibility of ACC draw down balancing


- Possibility of installing appropriately sized orifices on all down coming air extraction lines (Design dependent)
- Possibility of using NCG temperatures to control motorised valves to balance the extraction across the dephlegmators (Under investigation)



05 Air-Cooled Condenser Operation

Additional Means of Effective Operation:

- Effective ACC Cleaning
 - PID or MPC control
 - Dynamic load following control
 - Staggered fan start/stop logic
 - Ambient compensated control
 - Fan Zoning/grouping



06 Dissolved Oxygen

Dissolved Oxygen:

What are the typical misconceptions when it comes to DO levels?

- “if the vacuum is good, we do not have high DOs”
- “If the vacuum is bad , we must have high DOs” but,

What is good industry practices when it comes to managing high DO levels?

- Monitor both Vacuum and DO concentration
- Use partial pressure analysis to verify how much of the vacuum consists of air.
- Ensure effectiveness of air removal system
- Conduct regular Air Inleakage testing



07 Broad Spectrum Approach

What do we mean with a “Broad Spectrum Approach”?

”Adopting a strategy or methodology that addresses a wide range of conditions, variables, risks or scenarios in stead of focusing on one specific case, issue or solution”

Proposed Broad Spectrum Approach:

- Increase involvement of equipment owners on ACC design
- Investigate all associated equipment sets with a direct performance impact on the ACCs
- Consult with highly qualified air-inleakage specialists in conjunction with plant optimization specialists from the start to provide an informed view of the ACC and associated equipment performance

